

**(air-to-air air conditioners)**

(\*) If  $C_{dc}$  is not determined by measurement then the default degradation coefficient air conditioners shall be 0,25. (\*\*) From 26 September 2018. Where information relates to multi-split air conditioners, the test result and performance data may be obtained on the basis of the performance of the outdoor unit, with a combination of indoor unit(s) recommended by the manufacturer or importer.

**Information requirements  
(heat pump)**

Model(s): GMV-280WL/C1-X							
Outdoor side heat exchanger of heat pump	air						
Indoor side heat exchanger of heat pump	air						
Indication if the heater is equipped with a supplementary heater	no						
If applicable: driver of compressor	electric motor						
Parameters declared for	Average climate condition						
Item	symbol	value	unit	Item	symbol	value	unit
Rated heating capacity	$P_{rated,h}$	28.00	kW	Seasonal space heating energy efficiency	$\eta_{s,h}$	184.2	%
Declared heating capacity for part load at indoor temperature 20 °C and outdoor temperature $T_j$				Declared coefficient of performance for part load at given outdoor temperatures $T_j$			
$T_j = -7\text{ °C}$	$P_{dh}$	15.40	kW	$T_j = -7\text{ °C}$	$COP_d$	2.75	-
$T_j = +2\text{ °C}$	$P_{dh}$	9.50	kW	$T_j = +2\text{ °C}$	$COP_d$	4.20	-
$T_j = +7\text{ °C}$	$P_{dh}$	6.10	kW	$T_j = +7\text{ °C}$	$COP_d$	7.50	-
$T_j = +12\text{ °C}$	$P_{dh}$	5.80	kW	$T_j = +12\text{ °C}$	$COP_d$	9.50	-
$T_{biv}$ = bivalent temperature	$P_{dh}$	15.40	kW	$T_{biv}$ = bivalent temperature	$COP_d$	2.75	-
$T_{OL}$ = operation limit	$P_{dh}$	18.00	kW	$T_{OL}$ = operation limit	$COP_d$	2.61	-
$T_j = -15\text{ °C}$ (if $T_{OL} < -20\text{ °C}$ )	$P_{dh}$	-	kW	$T_j = -15\text{ °C}$ (if $T_{OL} < -20\text{ °C}$ )	$COP_d$	-	-
Bivalent temperature	$T_{biv}$	-7.00	°C	Operation limit temperature	$T_{ol}$	-10.00	°C
Degradation co-efficient heat pumps(**)	$C_{dh}$	0.25	—				
Power consumption in modes other than 'active mode'				Supplementary heater			
Off mode	$P_{OFF}$	0.030	kW	Back-up heating capacity (*)	$elbu$	0	kW
Thermostat-off mode	$P_{TO}$	0.055	kW	Type of energy input	Electric		
Crankcase heater mode	$P_{CK}$	0.045	kW	Standby mode	$P_{SB}$	0.030	kW
Other items							
Capacity control	variable			air flow rate, outdoor measured	—	11000	m³/h
Sound power level, indoor/outdoor measured	$L_{WA}$	-82.00	dB				
Emissions of nitrogen oxides (if applicable)	$NO_x(***)$	-	mg/kWh input GCV	Rated brine or water flow rate, outdoor side heat exchanger	—	-	m³/h
GWP of the refrigerant	2088		kg CO <sub>2</sub> eq (100 years)				
Contact details: West Jinji Rd, Qianshan, Zhuhai, Guangdong, China, 519070				Name of manufacturer: GREE ELECTRIC APPLIANCES, INC. OF ZHUHAI			
(*) (**) If $C_{dh}$ is not determined by measurement then the default degradation coefficient of heat pumps shall be 0,25. (***) From 26 September 2018. Where information relates to multi-split heat pumps, the test result and performance data may be obtained on the basis of the performance of the outdoor unit, with a combination of indoor unit(s) recommended by the manufacturer or importer.							

### Information requirements (heat pump)

Model(s): GMV-280WL/C1-X							
Outdoor side heat exchanger of heat pump	air						
Indoor side heat exchanger of heat pump	air						
Indication if the heater is equipped with a supplementary heater	no						
If applicable: driver of compressor	electric motor						
Parameters declared for	Warmer climate condition						
Item	symbol	value	unit	Item	symbol	value	unit
Rated heating capacity	$P_{rated,h}$	28.00	kW	Seasonal space heating energy efficiency	$\eta_{l\ s, h}$	263.8	%
Declared heating capacity for part load at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance for part load at given outdoor temperatures Tj			
Tj = - 7 °C	Pdh	-	kW	Tj = - 7 °C	COPd	-	-
Tj = + 2 °C	Pdh	21.00	kW	Tj = + 2 °C	COPd	2.80	-
Tj = + 7 °C	Pdh	14.00	kW	Tj = + 7 °C	COPd	6.00	-
Tj = + 12 °C	Pdh	6.20	kW	Tj = + 12 °C	COPd	8.70	-
Tbiv = bivalent temperature	Pdh	21.00	kW	Tbiv = bivalent temperature	COPd	2.80	-
TOL = operation limit	Pdh	21.00	kW	TOL = operation limit	COPd	2.80	-
Tj = - 15 °C (if TOL < - 20 °C)	Pdh	-	kW	Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	-
Bivalent temperature	Tbiv	2.00	°C	Operation limit temperature	Tol	2.00	°C
Degradation co-efficient heat pumps(**)	Cdh	0.25	—				
Power consumption in modes other than ‘active mode’				Supplementary heater			
Off mode	P <sub>OFF</sub>	0.030	kW	Back-up heating capacity (*)	elbu	0	kW
Thermostat-off mode	P <sub>TO</sub>	0.055	kW	Type of energy input	Electric		
Crankcase heater mode	P <sub>CK</sub>	0.045	kW	Standby mode	P <sub>SB</sub>	0.030	kW
Other items							
Capacity control	variable			air flow rate, outdoor measured	—	11000	m³/h
Sound power level, indoor/outdoor measured	L <sub>WA</sub>	-/82.00	dB				
Emissions of nitrogen oxides (if applicable)	NOx(***)	-	mg/kWh input GCV	Rated brine or water flow rate, outdoor side heat exchanger	—	-	m³/h
GWP of the refrigerant	2088		kg CO <sub>2</sub> eq (100 years)				
Contact details: West Jinji Rd, Qianshan, Zhuhai, Guangdong, China, 519070				Name of manufacturer: GREE ELECTRIC APPLIANCES,INC. OF ZHUHAI			

(\*)

(\*\*) If Cdh is not determined by measurement then the default degradation coefficient of heat pumps shall be 0,25.

(\*\*\*) From 26 September 2018.

Where information relates to multi-split heat pumps, the test result and performance data may be obtained on the basis of the performance of the outdoor unit, with a combination of indoor unit(s) recommended by the manufacturer or importer.